Design Transfer

Prozess Innensicht eines Inverkehrbringers: Spezifische Vorgaben und Umsetzung anhand eines Praxis-Beispiels

Andreas Born Group Leader Continuous Improvement Development SDIS

Disclaimer

All shown information regarding tolerances, distributions and other technical details do not represent reality 100%.


The numbers (e.g. tolerances) are typical for the dental implant field and shall help to understand the leverage arm, design transfer can have.

Design Transfer

- Design transfer is the process of transferring product design information (Product Specifications) to Manufacturing so that the input requirements meet the process output
- The product specification will be transferred to the manufacturing site where they produce Functional Samples, Prototypes, Zero Series Production Units.

Design Transfer within development projects

- The best practices include coordination with manufacturing early in the design process to ensure that design decision take into consideration manufacturability.
- Effective design transfer can lower material and production costs, decrease product time to market, increase product quality.



#WeRockDentistry – literally.

Performance

Cost Of Goods Sold
Raw materials, machining,
warehousing, direct labor costs,
factory overhead expenses

 GROUP KEY FIGURES
 (in CHF million)

 Change (%)

 Change (%)

 Gross profit
 840
 719
 17

 EBITDA
 324
 259
 25

 Operating profit (EBIT)
 284
 227
 26

 excl. exceptionals
 286
 227
 26

 Net profit
 276
 230
 20

 Cash generated from operating activities
 217
 185
 18

 Capital expenditure
 73
 47
 57

+16%
REVENUE GROWTH (organic)

OPerating EXpenses
Offices, salary, licenses,
travel expenses, etc.

Gross Margin

OPEX = EBIT

Earnings before Interests and Taxes



Straumann Portfolio in 2017

- 3000+ articles (implants, prosthetic components, instruments and auxiliaries)
- Implants in 3 different materials launched (titanium grade 4, TiZr und ZrO2
- 9 implant/prosthetic interfaces established
- Various prosthetic concepts (cement retained, screw retained, Variobase, etc.)



Tissue Level


Wide Neck (WN)
Regular Neck (RN)
Narrow Neck Crossfit (NNC)

Bone Level

Regular Crossfit (RC) Narrow Crossfit (NC)

PURE

Regular diameter (RD) Narrow diameter (ND)







Launch screw retained abutments

- •2015 -> 58 SKU
- •2017 -> 91 SKU











Launch VarioBase

•2014 -> 15 SKU

•2017 -> 51 SKU



Bone Level Prosthetic Portfolio

•2017 -> 305 SKU




























Acceptance criteria


Rotational freedom for screw retained interfaces ≤ 5°.












Process Capability

Cp 1.18 / Cpk 1.05

$$Cpk \ge 1.33 = 4\sigma$$

$$Cpk \ge 2.00 = 6\sigma$$





Performance highlights 2017

25%



Net Revenue	- COGS =	Gross N	largin
Gross profit	840		17
EBITDA	_10/24	259	
Operating profit (EBIT)	1034	227	26
excl. exceptionals	286	227	26
Net profit		230	20
Cash generated from operating activities		185	18
Capital expenditure		+0.2	5 % 57
Free cash flow		139	9
Basic EPS (in CHF)		14.68	20
Employees (at year end)		Gross	Marqu



Take home message

- Design transfer can be triggered by development and production
- Design transfer is a continuous step and shall not come to an end
- Product portfolios which grow over time must be assessed regarding the optimisation of the design, since the impact of reduced COGS can be significant
- All produts (especially big portfolios) must be assessed, if requirements change

